



Product Specification Sheet

Product Code: **1CHL-0350**

Item: **350kW Air Cooled Chiller**



Description:

The 350Kw Air Cooled Chilled includes an integrated hydronic module and a standard electrical disconnect switch. Exceptional quiet operation, the unit has a scroll compressor and low noise shrouded Flying Bird fans with 2 speed fan motors. User friendly Prodialog Plus control with direct display machine main parameters: temperatures, pressures, operating conditions. Easy integration into any building thanks to reduces footprint and low profile.

Features: Economical operation, Environmental care, Low operating sound levels

Accessories:

- Cable Cross Over - Lane
- Framed Lattice Panels
- Distribution Boards
- Chilled Water Pipe work
- Chilled Water Pumps
- Chilled Water Strainer

Technical Information:

Total Cooling Capacity (kW): **305**
Heating Capacity (kW): **0**
Stages: **0**
Air Flow (l/s): **0**
Refrigerant: **R134A**

Physical Information:

Height (mm): **2297**
Width (mm): **2253**
Length (mm): **3604**
Weight (kg): **3820**

Power Requirements:

Power Requirements: **400-3-50 V-Ph-Hz**
Separate Circuit Required:
Required Curcuit Breaker (amps): **0**

Thursday, 24 August 2017. This is a uncontrolled document for information purposes only.
© All content Copyright Aircon Rentals Pty Ltd. Aircon Rentals Pty Ltd is constantly seeking ways to improve the specifications, design and production of its products and alterations take place continually. Whilst every effort is made to produce up to date literature this brochure should not be regarded as an infallible guide to current specifications, nor does it constitute an offer for the sale of any particular product.

Aircon Rentals

PTY. LTD. ABN: 65 003 454 680

Sydney | Melbourne | Brisbane | Perth | Adelaide | Hobart | Canberra

Contact Us: **1800 626 996** | www.aircon.com.au